

### 3.7 Technical data ProSpray 24

<b>Voltage:</b>	220-240 V AC, 50/60 Hz or 100-120 V AC, 50/60 Hz
<b>Max. current consumption:</b>	
230 V AC	7 A
100-120 V AC	12 A
<b>Power cord:</b>	3 x 1.5 mm <sup>2</sup> – 6 m
<b>Acceptance capacity:</b>	1100 Watts
<b>Max. operating pressure:</b>	23 MPa (230 bar)
<b>Volume flow at 12 MPa (120 bar) with water:</b>	2.2 l/min
<b>Max. tip size:</b>	0.024 inch – 0.61 mm
<b>Max. temperature of the coating material:</b>	43°C
<b>Max. viscosity:</b>	25.000 MPa·s
<b>Filter insert (standard outfitting)</b>	60 mesh
<b>Weight:</b>	25 kg
<b>Special high-pressure hose:</b>	DN 6 mm, 15 m connecting thread M 16 x 1.5
<b>Dimensions (L x W x H)</b>	
Upright cart unit:	580 x 565 x 760 mm
Low boy cart unit:	820 x 430 x 545 mm
Stand unit	480 x 345 x 405 mm
<b>Max. sound pressure level:</b>	80 dB (A) *

\* Place of measuring: 1 m in distance from the unit and 1.6 m above the floor, 12 MPa (120 bar) operating pressure, reverberant floor.