

Robust and userfriendly for small road repair jobs or cutting small trenches for piping.
The alternative solution to a cut off saw on cart.
Compact - Lightweight - Quiet - Stable



6,5 HP Honda gas engine
Blade-ø 350mm
Cutting depth 120 mm

- Adjustable anti vibration handles for operators comfort
- Cutting depth adjustment by handwheel
- Cutting depth indicator
- Front cutting guide
- Parking break
- Lifting frame
- 25 Liter water tank, easy to fill
- Big rear wheels for good chassis clearance
- Durable Poly-V belt for an optimum of power transmission



Parking break



Adjustable anti vibration handles for operators comfort



Cutting depth locking device

Specifications	GÖLZ FS125
Max Cutting depth	120 mm
Blade diameter	350 mm
Shaft size	25,4 mm
Water tank	25 Liter
Engine	Honda GX200
Engine power (net power)	6,5HP/4,8 kW (5,5HP/4,1kW)
Shaft speed	2.730 min ⁻¹
Feed motion	Push
Cutting depth adjustment	Handwheel
Power transmission	Poly-V Belt
Hand Arm Vibrations	4,5 m/s ²
Dimensions (LxWxH)	650 x 450 x 1000 mm
Weight	77 kg
Order number	0282 125 6000



Motorstop



Cutting depth indicator



Lifting frame



Attachable water tank, easy to fill



Cutting depth adjustment by handwheel

Diamond Blades

Diamond Blades for Asphalt and Concrete, please check our Diamond Tools catalogue.