

Compact and solid Push Saw for small services and repair jobs in roadworks. The height adjustable Anti-Vibration Handles have a clear focus on operators convenience. Compact - Robust - Comfortable.



13 HP Honda gas engine
Blade-ø 450mm
Cutting depth 165 mm

- Adjustable anti vibration handles for operators comfort
- Cutting depth adjustment by handwheel
- Cutting depth indicator
- Front cutting guide
- Parking break
- Lifting frame
- 25 Liter water tank, easy to fill
- Big rear wheels for good chassis clearance
- Durable Poly-V belt for an optimum of power transmission



Parking break



Adjustable anti vibration handles for operators comfort



Cutting depth locking device

Specifications	GÖLZ FS175
Max Cutting depth	165 mm
Blade diameter	450 mm
Shaft size	25,4 mm
Water tank	25 Liter
Engine	Honda GX390
Engine power (net power)	13HP/9,5kW (11,8HP/8,7kW)
Shaft speed	2.300 min ⁻¹
Feed motion	Push
Cutting depth adjustment	Handwheel
Power transmission	Poly-V Belt
Hand Arm Vibrations	4,5 m/s ²
Dimensions (LxWxH)	1.220 x 491 x 1.160 mm
Weight	110 kg
Order number	0282 175 6000



Motorstop



Cutting depth indicator



Lifting frame



Attachable water tank, easy to fill



Cutting depth adjustment by handwheel

Diamond Blades

Diamond Blades for Asphalt and Concrete, please check our Diamond Tools catalogue.