

SPECIFICATIONS

Item	Model	C10FSH / C10FSB				
Motor	Type	Series commutator motor				
	Power source	Single-phase AC 50Hz				
	Voltage (Volts)	(230V, 240V) \surd				
	Power input	1450W				
Laser Marker (Only Model C10FSH)	Maximum output	<1mW CLASS II Laser Product				
	Wave length	400~700 nm				
	Laser medium	Laser Diode				
Applicable saw blade	Outside Dia. 262mm (10") Hole Dia. 25.4mm (1") or 30mm (1-3/16") (Only Model 240V)					
No load speed	3800/min					
Max. sawing dimension	Miter	Head	Turntable	Max. sawing dimension		
		0	0	Max. Height	88mm	(3-15/32")
				Max. Width	312mm	(12-9/32")
				* Max. Height	91mm	(3-19/32")
				Max. Width	300mm	(11-13/32")
		0	Left 45° or Right 45°	Max. Height	88mm	(3-15/32")
				Max. Width	218mm	(8-19/32")
				* Max. Height	91mm	(3-19/32")
				Max. Width	200mm	(7-7/8")
				With aux. board	10mm	(13/32")
		0	Right 57°	Max. Height	88mm	(3-15/32")
				Max. Width	165mm	(6-1/2")
				* Max. Height	91mm	(3-19/32")
				Max. Width	150mm	(5-29/32")
				With aux. board	10mm	(13/32")
	Bevel	Left 45°	0	Max. Height	56mm	(2-7/32")
				Max. Width	305mm	(12")
				* Max. Height	61mm	(2-13/32")
				Max. Width	290mm	(11-13/32")
				With aux. board	10mm	(13/32")
		Right 45°	0	Max. Height	31mm	(1-7/32")
				Max. Width	305mm	(12")
				* Max. Height	36mm	(1-13/32")
				Max. Width	290mm	(11-13/32")
				With aux. board	10mm	(13/32")
	Compound	Left 45°	Left 45° or Right 45°	Max. Height	56mm	(2-7/32")
				Max. Width	218mm	(8-19/32")
				* Max. Height	61mm	(2-13/32")
				Max. Width	200mm	(7-7/8")
				With aux. board	10mm	(13/32")
		Right 45°	Left 31°	Max. Height	31mm	(1-7/32")
				Max. Width	260mm	(10-7/32")
				* Max. Height	36mm	(1-13/32")
				Max. Width	248mm	(9-3/4")
				With aux. board	10mm	(13/32")
		Right 45°	Right 45°	Max. Height	31mm	(1-7/32")
				Max. Width	218mm	(8-19/32")
				* Max. Height	36mm	(1-13/32")
				Max. Width	200mm	(7-7/8")
				With aux. board	10mm	(13/32")
Miter sawing range	Left 0° – 45° Right 0° – 57°					
Bevel sawing range	Left 0° – 45° Right 0° – 45°					
Compound sawing range	Left (Bevel) 0° – 45°, Left and Right (Miter) 0° – 45°					
	Right (Bevel) 0° – 45°, Left (Miter) 0° – 31°, Right (Miter) 0° – 45°					
Net weight	19.5kg (43 lbs.)					
Cord	2 Conductor type cable 1.8m (6ft.)					